

AR60M

TIPO -MODEL	AR60M	Dimensioni Dimensions	Ø Int. Min Inside Diameter
1		70 x 10 25 x 5 2-3/4" x 3/8" 2-1" x 0.2"	1,500 500 59" 20"
2		100 x 20	1,400
		4" x 3/4"	55"
3		38	500
		1-1/2"	20"
4		35	500
		1-3/8"	20"
5		60 x 3	1,000
		2-3/8" x 0.120"	40"
6		70 x 20 x 3	1,000
		2-3/4" x 3/4" x 0.107"	40"
7		50 x 3	1,500
		2" x 0.120"	59"
8		60 x 6 30 x 4	1,800 500
		2-3/8" x 0.240" 1-1/8" x 0.157"	70" 20"
9		60 x 60 x 6 30 x 4	1,000 500
		2-3/8" x 0.240" 1-1/8" x 0.157"	40" 20"
10		60	1,000
		2-3/8"	40"
11		60	1,000
		2-3/8"	40"
12		60	1,000
		2-3/8"	40"
13		80x45	1,000
		3-1/8" x 1-3/4"	40"
14		80x45	1,000
		3-1/8" x 1-3/4"	40"
15		IPE	
16		HE	
17		UNP	
18		IPE	
19		HE	
Wcm ³ Max		25	25
Velocità di rotolamento Inches / min speed		5	237
Potenza Kw HP Power		3	4
Ø alberi Shafts diameter	mm. "	60 2.375"	
Ø rulli Rolls diameter	mm. "	215 8.46"	
Peso Weight	Kg. Lbs.	920 2,026	



TIPO -MODEL	AR80M	Dimensioni Dimensions	Ø Int. Min Inside Diameter
1		90 x 15 80 x 18 3-9/16" x 1/2" 3-1/8" x 3/4"	1,500 800 59" 32"
2		120 x 30	800
		4-5/8" x 1-1/8"	32"
3		50	600
		2"	24"
4		60	600
		2-3/8"	24"
5		88,9 x 3	1,800
		3-1/2" x 0.120"	72"
6		90 x 10	1,000
		3-9/16" x 3/8"	40"
7		70 x 70 x 4	1,000
		2-3/4" x 2-3/4" x 0.157"	40"
8		80 x 10 30 x 4	1,800 460
		3-1/8" x 3/8" 1-1/8" x 0.157"	72" 18"
9		70 x 8 30 x 4	1,000 460
		2-3/4" x 3/8" 1-1/8" x 0.157"	35" 18"
10		80 x 9	1,300
		3-1/8" x 0.354"	52"
11		80 x 9	1,300
		3-1/8" x 0.354"	52"
12		80 x 9	1,300
		3-1/8" x 0.354"	52"
13		120	1,000
		4-5/8"	40"
14		120	1,000
		4-5/8"	40"
15		120	1,200
		4-5/8"	47"
16		HE	
17		UNP	
18		INP	
19		HE	
Wcm ³ Max		40	40
Velocità di rotolamento Inches / min speed		5	237
Potenza Kw HP Power		4	5.5
Ø alberi Shafts diameter	mm. "	80 3.15"	
Ø rulli Rolls diameter	mm. "	265 10.43"	
Peso Weight	Kg. Lbs.	1,650 3,630"	

AR80M

